

Residential Construction Post Test Answers

On the answer sheet, please fill in the correct answer to the following questions.

1. A fully enclosed chute shall be used when materials are dropped more than 20 feet to a point outside the building.
a. True
b. False

2. Ground Fault Circuit Interrupters (GFCI) must be used on all 120 volt, single phase, 15 and 20 ampere receptacle outlets.
a. True
b. False

3. The standards regulating fall protection systems used on roofs change at what pitch?
a. 4/12
b. 5/12
c. 8/12
d. None of the above

4. OSHA's standards require extension ladders be placed at a 4 ½ to 1 ratio.
a. True
b. False

5. A Personal Fall Arrest System (safety harness & lanyard) must have a proper tie off point. That point must be rated at least 5000 pounds.
a. True
b. False

6. The maximum free fall allowed by OSHA is.
 - a. 4 feet
 - b. 6 feet**
 - c. 10 feet
 - d. 12 feet

7. Guardrail systems must have an upright member (or standard) every 6 feet.
 - a. True
 - b. False**

8. Type IA ladders are rated for _____ pounds.
 - a. 150
 - b. 200
 - c. 250
 - d. 300**

9. Steps or stairs of more than 30" in height must have a stair rail or guardrail.
 - a. True**
 - b. False

10. While placing decking or installing outside walls on the second floor of a residence, workers are exempt from fall protection standards.
 - a. True
 - b. False**