

Hispanic Contractors Association de San Antonio
Fall Protection for the Construction Industry (SH-22298-11-60-F-48)
PRE-TEST

Name: _____ Date: _____

1. Anchorage points must be able to support a weight of at least _____ per worker attached.
 - a. 400 lbs.
 - b. 1,500 lbs.
 - c. 10,000 lbs.
 - d. 5,000 lbs.
2. *True or False?* Engineering controls, such as scaffolds and guardrails, should be used to eliminate the fall hazard whenever possible.
3. *True or false?* A low-slope roof has a slope of 4 to 12 (vertical to horizontal).
4. By law, fall protection in the construction industry is required when working at least _____ feet above a lower level.
5. *True or false?* When using an extension ladder, the ratio of how far the base of the ladder needs to be from the building or the wall? (Vertical to horizontal) is 2:1
6. Top guardrails need to be placed at _____ inches from the floor and be able to withstand a force of at least _____ lbs.
7. A personal fall arrest system is made up of:
 - a. Body belt, rope & carabineer
 - b. Waist harness, rope & guardrails
 - c. Full body harness, lanyard & anchors
 - d. Guardrails, yo-yo & body belt
8. The _____ in a scaffold prevent tools and materials from falling to lower levels.
9. *True or false?* A 6 ft. lanyard/connector can be used when working on the second level of a scaffold (approximately 12 to 13ft. high).
10. *True or False?* A harness can be reused after a fall.