

ITEMS TO BE CONCERNED WITH IN THE SHOP/GARAGE

1. Loft storage areas have a proper four inch toe board.
2. Stairway to loft storage areas shall have a proper railing and intermediate railing.
3. The loft storage areas shall have a property railing and intermediate railing.
4. Oxygen and acetylene tanks shall be held secure in an upright position.
5. Oxygen and acetylene tanks shall be stored 20 feet apart when inside a building.
6. Oxygen and acetylene tanks on welding cart shall have back flow check valves.
7. Air pressure for cleaning of parts is not to be greater than 30 PSI.
8. Portable fire extinguishers shall not be obstructed.
9. Air hoses, welding hoses and extension cords or drop cords cannot be across the common path of travel.
10. If there is a service pit, check chains should be on both sides and in front and back of pit area.
11. Batter charge area should have rubber gloves, rubber apron, face protection, and some type of portable eye wash.
12. Bench grinders tool rest shall be no more than 1/8 inch from the face of the wheel.
13. Pedestal grinders shall be held secure to the floor.
14. Pedestrian exit doors shall not be obstructed.
15. The main electrical controls shall not be obstructed.
16. Main electrical control switches shall be labeled as to what they control.
17. Electrical extension cords shall not have cuts or broken ground plug or exposed wire.
18. Trouble lights shall not be bare bulbs. They must have a bulb cage.
19. Gas cans shall be of the explosion-proof type.
20. Drive belts and pulleys less than seven feet from the floor shall have a proper guard.
21. Chains used for lifting shall have a load limit tag on them.

22. Barrels of oil, hydraulic oil, and other chemicals shall be properly stored and have drip pans.
23. Fans less than seven feet from the floor shall have a guard with openings no larger than 1/2 inch.
24. Parts washer cover must have a self-closing lid with fusible link.
25. Chains used for lifting shall not have elongated or twisted hooks.
26. Chains used for lifting shall not have elongated or repaired links.
27. Common path of travel shall not be obstructed.
28. Grinder wheels shall be guarded on both sides.
29. Class A combustible trash shall be in metal containers.
30. If you do painting, paint cans should be stored in proper fire-proof cabinet or quantity of paints on hand be reduced.
31. Split rim tires shall be inflated in a safety tire cage.
32. Sweeping compound shall be used on spilled oil, grease, hydraulic fluid, and the like.
33. Oil and grease rags shall be disposed of in a covered metal container.
34. Step ladders shall have no broken rungs, split side rails, or broken metal hardware.
35. Extension ladders shall have non-skid feet and no broken steps or side of rails.
36. Good housekeeping shall be maintained and work areas clean and orderly.
37. Portable fire extinguishers shall be no more than 50 feet travel distance.