

Pre-Program Assessment Answers

1. What OSHA Regulations apply to warehouse worker activities?
A. OSHA 90.1 (2007)
B. OSHA 1910
C. OSHA 1926
D. OSHA 2000
2. What was the most frequently cited OSHA violation in steel fabrication facilities (2012)?
A. Electrical Lockout/tagout
B. Powered Industrial Trucks (forklifts)
C. Respiratory Protection
D. General Requirements
3. What was the most frequently cited OSHA Regulation in general warehousing?
A. Forklifts
B. Portable fire extinguishers
C. Exits
D. Electrical Lockout/tagout
4. Which tool below should be used to remove metal banding straps from bundled material?
A. Hammer
B. Long Crowbar
C. Scissors
D. Long handled shears
5. At what maximum height should some form of protection from falls be provided for workers when working on platforms?
A. 2 feet
B. 4 feet
C. 6 feet
D. 8 feet
6. How frequently should crane parts such as hydraulic lines, pumps and hooks be inspected for maladjustment, deterioration, leakage deformation or other damage?
A. Daily
B. Weekly
C. Monthly
D. Yearly

This material was produced under grant number SH-26316-SH4 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trades names, commercial products, or organizations imply endorsement by the U.S. Government.

Warehouse Worker Hazards in Structural Steel Fabricating and Supply Companies-Train the Trainer Session

7. Which of the following statements is true
- A. Crane operators must be “certified” to operate a crane in the fabrication shop
 - B. Crane operators are not required to be certified to operate a crane in the fabrication shop, but if they operated a crane at a construction site they would need to be certified.**
 - C. Crane operators are not required to be certified
8. When “backing up” trucks for offloading materials “spotters” should stand in which location?
- A. Behind the truck toward the middle
 - B. To the side of the truck toward the rear**
 - C. In front of the truck
 - D. In the space between the truck and an overhead door
9. Which of the following is true when leaving a Powered Industrial Truck (forklift) unattended?
- A. The load engaging means should be fully raised
 - B. The load engaging means should be fully raised and the engine turned off
 - C. The load engaging means should be full lowered and engine left running
 - D. The load engaging means should be fully lowered and the engine shutoff**
10. **!** This symbol on a product label indicates which of the following
- A. Explosives
 - B. Acute toxicity (Severe)
 - C. Acute Toxicity (Less severe)**
 - D. Gas under pressure
11. SDS sheets must be accessible in hard copy paper form in a location that is accessible to employees.
- A. True
 - B. False**
12. Musculoskeletal Disorders (MSDs) account for what percentage of lost or restricted work time?
- A. about 1/10
 - B. about 1/4
 - C. about 1/3**
 - D. about 2/3

This material was produced under grant number SH-26316-SH4 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trades names, commercial products, or organizations imply endorsement by the U.S. Government.

Warehouse Worker Hazards in Structural Steel Fabricating and Supply Companies-Train the Trainer Session

13. In order to decrease injuries from lifting heavy objects which muscle groups should be primarily used?
- A. Leg muscles
 - B. Back muscles
 - C. Abdominal muscles
14. H.A.V.S. is an abbreviation which is related to which of the following?
- A. A classification for Industrial Powered Trucks
 - B. An electrical voltage rating system
 - C. A syndrome caused by vibration
 - D. Hand eye coordination
15. Arc flash can occur even when two energized parts are not connected by a physical wire.
- A. True
 - B. False
16. For a respirator which must be fit tested, how frequently should a “seal check” be performed?
- A. Each time it is worn
 - B. Daily
 - C. Weekly
 - D. Monthly
17. Respirators, filters and cartridges must be certified by which organization?
- A. ANSI
 - B. ASTM
 - C. NIOSH
 - D. OSHA
18. An employer is considering two forms of hearing protection. Product “A” has a NRR rating of 25 and the Product “B” has a NRR of 33. Which is the more effective hearing protection?
- A. Product “A”
 - B. Product “B”

This material was produced under grant number SH-26316-SH4 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trades names, commercial products, or organizations imply endorsement by the U.S. Government.