



Lifeline Installation & Use Post-Questionnaire

Choose the **ONE** best answer.

1. A bin entrant's responsibilities **do not** include communicating whether more or less slack is needed in the lifeline rope. **TRUE** **FALSE**
2. An observer should be present during bin entry
 - a. When the entrant is not wearing a lifeline
 - b. When the entrant is wearing a lifeline
 - c. When it is a commercial facility
 - d. When any bin entry occurs
3. A "capture system" is a mechanical device that anchors the lifeline by locking off the rope. **TRUE** **FALSE**
4. A secured lifeline system has:
 - a. Two anchor points at the peak (top) and side.
 - b. Two anchor points at opposite sides of the bin.
 - c. Two anchor points an equal distance from each other.
 - d. One anchor point at the peak (top) or side.
5. An **inappropriate** method to secure a lifeline is to attach it to the nearest, permanent structural component of the bin such as a ladder or conduit. **TRUE** **FALSE**
6. A lifeline must keep an entrant from
 - a. Sinking more than shoulder deep
 - b. Sinking more than chest deep
 - c. Sinking more than waist deep
 - d. Sinking more than knee deep
7. Lock out/Tag out (LOTO) should only be performed when a bin entrant IS wearing a lifeline. **TRUE** **FALSE**
8. A lifeline is most effective during a grain bin entry when it is:
 - a. A top entry
 - b. A side entry
 - c. Neither type of entry
 - d. Both types of entry
9. One of the observer's duties is to initiate a rescue if needed. **TRUE** **FALSE**
10. A harness should be:
 - a. Inspected & cleaned 2-4 times per year.
 - b. Inspected before each use & cleaned after each use.
 - c. Inspected after each use & cleaned before each use.
 - d. Inspected & cleaned once per year.