

TEMAPRIME ABCD

Date 01.15.2012

Previous date: 23.3.2006

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/ UNDERTAKING

- 1.1 Identification of the article**
- 1.1.1 Commercial Product Name**
TEMAPRIME ABCD
- 1.1.2 Product code**
006 7450 - 7452
- 1.2 Use of the Substance/Preparation**
- 1.2.1 Intended use**
Painting work
Description: An anti-corrosive pigmented alkyd primer for steel surfaces.
- 1.3 Identification of the company**
- 1.3.1 Supplier**
- 1.3.2 Contact information:**
P.O.Box
Postcode and post office
- Telephone
Telefax
- 1.3.4 Responsible for the Safety Data Sheet:**
- 1.4 Emergency telephone number**
- 1.4.1 Telephone number, name and address**

2. HAZARDS IDENTIFICATION

Flammable.

Dangerous for the environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Information on hazard labelling in section 15.1.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

3.1	Hazardous components		3.1.2	3.1.3	3.1.4
3.1.1	CAS number	EINECS	Chemical name of the substance	Concentration	Classification
	64742-48-9	265-150-3	Naphtha, hydrotreated heavy (aliphatic hydrocarbon solvent)	25 - 50 %	Xn; R10-65-66
	1330-20-7	215-535-7	Xylene	1 - 5 %	Xn; R10-20/21-38
	7779-90-0	231-944-3	Zinc phosphate	5 - 10 %	N; R50/53
	1314-13-2	215-222-5	Zinc oxide	1 - 5 %	N; R50/53
	96-29-7	202-496-6	Methylethylketoxime	< 0,5 %	Xn; R21-40-41-43

4. FIRST AID MEASURES

- 4.1 Additional advice**
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.

TEMAPRIME ABCD

Date 01.15.2012

Previous date: 23.3.2006

4.4 Eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

4.5 Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES**5.1 Suitable extinguishing media**

Use foam, CO₂, powder or water spray.

5.2 Extinguishing media which must not be used for safety reasons

Waterjet

5.3 Specific hazards

Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions**

Avoid breathing vapours. Exclude sources of ignition.

6.2 Environmental precautions

Do not allow to enter drains or water courses.

6.3 Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents. Note! Products containing oxidative drying oil or alkyd (linseed oil varnish, alkyd paints and -lacquers) have a possibility of auto-ignition in porous materials damped by the product. This kind of waste must be collected and stored e.g. in water before disposal or burning.

7. HANDLING AND STORAGE**7.1 Handling**

Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.

7.2 Storage

Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Exposure Limit Values****8.1.1 Occupational exposure limit values**

Xylene 100 ppm (8 h)

Zinc oxide 2 mg/m³ (8 h)

8.1.2 Information on limit values

TLV-TWA = Threshold Limit Values - Time-weighted average / ACGIH 2008

8.2 Exposure controls**8.2.1 Occupational exposure controls**

Provide adequate ventilation. Comply with the health and safety at work laws.

8.2.1.1 Respiratory protection

Use appropriate certified respirators, with gas and vapor filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapor and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

8.2.1.2 Hand protection

Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed

areas of the skin.

8.2.1.3 Eye protection

Safety eyewear must be used, specially during spray-application.

8.2.1.4 Skin and body protection

Protective clothing must be used during spray-application.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General Information (appearance, odour)

Coloured, viscous liquid, strong odour.

9.2 Important Health Safety and Environmental Information

9.2.2	Boiling point/range	145 - 200 °C *)
9.2.3	Flash point	36°C *)
9.2.5	Explosive properties	
9.2.5.1	Lower explosion limit	0,6 vol-% *)
9.2.5.2	Upper explosion limit	7,0 vol-% *)
9.2.7	Vapour pressure	0,2 kPa (20 °C) *)
9.2.8	Relative density	1,29 - 1,31
9.2.9	Solubility	
9.2.9.1	Water solubility	Insoluble
9.2.11	Viscosity	flow time more than 30 sec / ISO 3 mm cup
9.3	Other data	
	Evaporation rate (BuAc=1) : 0,14 *)	
	*) = Naphtha, hydrotreated heavy	

10. STABILITY AND REACTIVITY

10.1 Conditions to avoid

Solvent vapours may form explosive mixtures with air.

10.2 Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.3 Hazardous decomposition products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION

11.1 Acute toxicity

See section 11.5.

11.2 Primary irritation

See section 11.5.

11.3 Sensitisation

Contains methylethylketoxime. May produce an allergic reaction.

11.5 Human experience

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally.

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

12.1.1 Aquatic toxicity

Zinc oxide: EC50 = 0,17 mg/l, selenastrum capricornutum, 72 h; very toxic. Zinc phosphate:
LC50(fish) = 0,14-2,6 mg Zn2+/l;
EC50(48h, daphnia magna) = 0,04-0,86 mg Zn2+/l, EC50(72h, algae) = 0,136-0,150 mg Zn2+/l

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy per the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	1263
14.2	Packing group	III
14.3	Land transport	
14.3.1	ADR/RID Class	3
14.3.3	Description of the goods	paint
14.4	Sea transport	
14.4.1	IMDG Class	3
14.4.2	Proper shipping name	paint
14.4.3	Further Information	EmS: F-E,S-E
14.5	Air transport	
14.5.1	ICAO/IATA Class	3
14.5.2	Proper shipping name	paint

15. REGULATORY INFORMATION

15.1 Information on the warning label

15.1.1 Letter code of the warning symbol and indications of danger for the preparation

N Dangerous for the environment

15.1.2 Names of the ingredients given on the warning label

Naphtha, hydrotreated heavy
Zinc phosphate

15.1.3 R-phrases(s)

R10 Flammable.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

15.1.4 S-phrase(s)

S23 Do not breathe vapour/spray.
S29 Do not empty into drains.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

15.1.5 Special regulations on certain preparations

Contains methylethylketoxime. May produce an allergic reaction.

16. OTHER INFORMATION

16.1 Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R20/21	Harmful by inhalation and in contact with skin.
R21	Harmful in contact with skin.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitization by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

16.4

Additional information

The information of this SDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Signature