Fall Safety Prevention Training--POST-TEST

NAME	COMPANY	DATE

- 1. You can use any material to cover a hole during construction.
 - a. True
 - b. False
- 2. Since, they don't make any safety equipment available for roofers, as a roofer you don't need OSHA subpart M 1926.500 & 1926.501 –FALL PROTECTION- doesn't apply to roofing.
 - a. True
 - b. False
- 3. You can use a 2x12 as a walkway over an excavation.
 - a. <u>True</u>
 - b. False
- 4. It doesn't matter what you use for an anchorage point as long as you are tied off.
 - a. True
 - b. False
- 5. Skylights are safe to sit on.
 - a. True
 - b. False
- 6. How many points of contact are necessary for climbing a ladder?
 - a. 2
 - b. 3
 - c. 4
- 7. What are the top three major types of fall hazards in construction?
 - a. Trenches, roofs, tree trimming
 - b. Industrial piping, portable ladders, roofs
 - c. Tree trimming, trenches, portable ladders
 - d. Roofs, scaffolding, portable ladders
- 8. Scaffold builders are required fall protection when?
 - a. 4 foot above the lower level
 - b. 6 foot above the lower level
 - c. 10 foot above the lower level
 - d. Never, it's not necessary when building a scaffold
- 9. The top of the ladder must extend how high above the landing you are trying to access?
 - a. 1 foot
 - b. 2 foot
 - c. 3 foot
 - d. 4 foot
- 10. A personal fall arrest system consists of:
 - a. Full body harness and lanyard
 - b. Anchorage and body belt
 - c. Anchorage, full body harness, and lanyard/retractable lanyard
 - d. Anchorage, body belt, and lanyard/retractable lanyard
- 11. How many pounds per worker does an anchorage need to support?
 - a. 5,000
 - b. 3,000
 - c. 2,000

This material was produced under grant SH-31226-SH7 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does the mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government.

Fall Safety Prevention Training—POST-TEST - ANSWER KEY

NAME	COMPANY	DATE

- 1. You can use any material to cover a hole during construction.
 - a. True
 - b. <u>False</u>
- 2. Since, they don't make any safety equipment available for roofers, as a roofer you don't need OSHA subpart M 1926.500 & 1926.501 –FALL PROTECTION- doesn't apply to roofing.
 - a. True
 - b. <u>False</u>
- 3. You can use a 2x12 as a walkway over an excavation.
 - a. <u>True</u>
 - b. False
- 4. It doesn't matter what you use for an anchorage point as long as you are tied off.
 - a. True
 - b. <u>False</u>
- 5. Skylights are safe to sit on.
 - a. True
 - b. <u>False</u>
- 6. How many points of contact are necessary for climbing a ladder?
 - a. 2
 - b. <u>3</u>
 - c. 4
- 7. What are the top three major types of fall hazards in construction?
 - a. Trenches, roofs, tree trimming
 - b. Industrial piping, portable ladders, roofs
 - c. Tree trimming, trenches, portable ladders
 - d. Roofs, scaffolding, portable ladders
- 8. Scaffold builders are required fall protection when?
 - a. 4 foot above the lower level
 - b. 6 foot above the lower level
 - c. 10 foot above the lower level
 - d. Never, it's not necessary when building a scaffold
- 9. The top of the ladder must extend how high above the landing you are trying to access?
 - a. 1 foot
 - b. 2 foot
 - c. <u>3 foot</u>
 - d. 4 foot
- 10. A personal fall arrest system consists of:
 - a. Full body harness and lanyard
 - b. Anchorage and body belt
 - c. Anchorage, full body harness, and lanyard/retractable lanyard
 - d. Anchorage, body belt, and lanyard/retractable lanyard
- 11. How many pounds per worker does an anchorage need to support?
 - a. <u>5,000</u>
 - b. 3,000
 - c. 2,000

This material was produced under grant SH-31226-SH7 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does the mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government.