

Name: _____ **Date:** _____

Fall Prevention Post Test

- 1. Who is primarily responsible for providing employees with a fall protection system?**
 - A. The manufacturer of the fall protection system
 - B. The employer
 - C. The employee
 - D. The insurer

- 2. You should report an accident immediately after it occurs so that _____**
 - A. Someone else can use the machine
 - B. First-aid can be applied if necessary
 - C. Everyone else can see what's going on
 - D. Your supervisor can hide the evidence

- 3. The ultimate responsibility for on-the-job safety rests with _____**
 - A. You
 - B. Your supervisor
 - C. Human resources
 - D. OSHA

- 4. The most common causes of injury on a construction site are _____**
 - A. Fires
 - B. Choking
 - C. Falls
 - D. Faulty equipment

- 5. Inspections of scaffolds must be conducted?**
 - A. By a competent person
 - B. Before each work shift
 - C. After scaffold is erected or modified
 - D. All of the above

- 6. A floor hole wider than _____ must be protected.**
 - A. 12 inches
 - B. 24 inches
 - C. 2 inches
 - D. 19 inches

- 7. A fall arrest system is required when a worker is operating at a height of ?**
 - A. 3 feet or more
 - B. 6 feet or more
 - C. 10 feet or more
 - D. None of the above

- 8. At what height do open-sided floors in construction require guardrails?**
 - A. 1 foot
 - B. 2 feet
 - C. 4 feet
 - D. 6 feet

Name: _____ Date: _____

Fall Prevention Post Test

9. If an employee falls into their fall protection equipment what should happen to the equipment.

- A. Inspect it and return to service if it is in good condition
- B. Take it out of service immediately
- C. If the employee was not injured cut it up and throw it away
- D. Save the equipment and only use it when you think someone might fall. It worked the first time so it should work the second time

10. An anchorage point for a Fall RESTRAINT system must be capable of supporting?

- A. 5,000 pounds
- B. 1,500 pounds
- C. 12,000 pounds
- D. 3,000 pounds

11. When fall arrest equipment is used, employers must assure that _____.

- A. All equipment is properly inspected before each use
- B. Users have calculated total fall distance
- C. A rescue plan is in place to rescue a fallen employee
- D. All of the above

12. What items and/or elements and/or approaches can be legally and safely used to help prevent falls during roof construction activities:

- A. Guardrails
- B. Covering holes and openings with sheathing
- C. Ensuring workers are properly and adequately trained
- D. All of the above

13. If you are going to step onto a platform or roof, the top of the ladder should extend at least _____ feet above the point where the ladder touches the upper landing surface.

- A. 2
- B. 3
- C. 4
- D. 5

14. A type 1A ladder is rated for _____ use.

- A. 200 pounds, light duty/household
- B. 225 pounds, medium duty/commercial
- C. 250 pounds, heavy duty/industrial
- D. 300 pounds, extra heavy duty/professional

15. When should ladders be inspected?

- A. Each day before use
- B. At least once a week
- C. At least once a month
- D. At least once a year