## **Amputation Prevention Quiz**

- T F 1. Machinery and machine guarding are designed to protect workers during normal production operations.
- T F 2. The three types of hazardous motion are rotating, reciprocating and transverse.
- T **F** 3. Power transmission apparatus is where work is performed on material such as rolling, cutting, forming or shaping.
- T F 4. Allowing for safe lubrication is one of the six a characteristics of an effective guard.
- T F 5. Nip points may result from parts rotating in opposite directions.
- T **F** 6. Lockout is necessary when servicing or cleaning equipment, but is an unnecessary step when clearing jams.
- T F 7. The engineers who design planers designed them to jam up so you have to stick your hands into the point of operation to free the jammed material.
- T F 8. If you are required to place any part of your body into an area on a machine or piece of equipment where work is actually performed on material or where an associated danger zone exists during a machine operating cycle, you must lockout.
- T F 9. Service and maintenance include unjamming, making adjustments and cleaning activities.
- T F 10. Lockout protects you during servicing and maintenance.

## Extra Credit

T F 11. It is your right to not operate equipment that has missing, damaged or inadequate guards.

This material was produced under grant SH-05031-SH8 from the Occupational Safety and Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government.