

NAME: _____ **PRE-TEST**

Quiz for walking and working surfaces

1. All scaffolds and their supports shall be capable of supporting the load designed with a safety factor of not less than:
 - a) 2
 - b) 3
 - c) 4
 - d) 5

2. Gratings, walkways, and catwalks, from which sections or ladders have been removed, shall be barricaded with adequate guardrails.
 - a) True
 - b) False

3. There shall be at least ___ safe and accessible ladder(s) in any cargo space which employees must enter.
 - a) 1
 - b) 2
 - c) 3
 - d) 4

4. All of the following are acceptable examples of lumber for scaffolds EXCEPT:
 - a) Spruce
 - b) Hemlock
 - c) Fir
 - d) Oregon Pine

5. Platform planking shall be of not less than _____ lumber.
 - a) 2 x 6-inch
 - b) 2 x 8-inch
 - c) 2 x 10-inch
 - d) 2 x 12-inch

6. Welding, burning, riveting or open flame work shall be performed on any staging suspended by means of fiber rope.
 - a) True
 - b) False

7. Employees shall be guarded from falls of more than ___ feet above a solid surface.
 - a) 3
 - b) 4
 - c) 5
 - d) 6

NAME: _____ **PRE-TEST**

8. The top rail of a fall protection system shall be between ___ and ___ inches.
 - a) 40:43
 - b) 41:44
 - c) 42:45
 - d) 43:46

9. Flush manholes and other small openings of comparable size in the deck and other working surfaces, such openings shall be suitably covered or guarded to a height of not less than ___ inches.
 - a) 27
 - b) 28
 - c) 29
 - d) 30

10. When conditions are such that a straight ladder cannot be used, a ___ may be used.
 - a) Fire ladder
 - b) Boatswain's chair
 - c) Scaffold
 - d) Jacob's ladder