Third Edition



Workplace Health and Safety Manuel

Chemical Hazards Machine Hazards

Chapters

Chemical Hazards – Page 7

Machine Hazards – Page 31

OSHA

Funding for this Workplace Health and Safety Manual was provided under grant SH-31206-SH7 from the U.S. Department of Labor, Occupational Safety and Health Administration (OSHA), Susan Harwood Grant program. The manual's contents do not necessarily reflect the view or policies of the U.S. Department of Labor, nor does the mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government.

It is not possible to include discussion of everything necessary to ensure a health and safe working environment in a manual of this nature. Thus, this information must be understood as a tool for addressing workplace hazards, rather than an exhaustive statement of an employer's legal obligations, which are defined by statute, regulations, and standards. Likewise, to the extent that this information references practices or procedures that may enhance health or safety, but which are not required by a statue, regulation, or standard, it cannot, and does not, create additional legal obligations.

Finally over time, OSHA rules and interpretations may be modified in light of new technology, information, or circumstances; to keep apprised of such developments, or to review information on a wide range of occupational safety and health topics, visit OSHA's website at www.osha.gov.

Western North Carolina Workers' Center

Western North Carolina Workers' Center's mission is to develop leadership among workers through organizing and education to resolve issues of labor rights and promote fair working conditions in Western North Carolina.

Illustrations

Mark Hurwitt Graphics

The Small Group Activity Method

Illustration Reflection

What is happening in the illustration on the cover of the manual? Who is leading the workshop and why? What are the learners doing?

Basic Structure

The Small Group Activity Method is based on activities. An activity can take from 45 minutes to an hour. Each activity has a common basic structure:

- Small Group Tasks
- Report-Back
- Summary

Small Group Tasks: Activities include tasks (problems), or sets of tasks, for the groups to work on. Each tasks asks that groups use their experience and the factsheets to solve problems and make judgments on key issues.

Report-Back: For each task, groups select scribes that take notes on the small group discussions and report back to the class as a whole. During the report back, the scribe informs the entire class as to how his or her group solved the particular problem. The trainer records each scribes report back on large pads of paper in front of the class so that everyone can refer to them.

Summary: Before the discussion drifts too far, the trainer needs to bring it all together during the summary. Here, the trainer highlights the key points of the Activity and brings up any problems or points that may have been overlooked during the report-back.

Three Basic Learning Exchanges

The Small Group Activity Method is based on the idea that every training is a space where learning is shared. With SGAM, learning is not a one-way street that runs from trainer to worker. Rather, SGAM is a structured procedure that allows us to share information. It is based on three learning exchanges:

- Worker-to-Worker
- Worker-to-Trainer
- Trainer-to-Worker

Worker-to-Worker: Most of learn best from each other. SGAM is structured so that the worker-to-worker exchange is a key element of the training. The worker-to-worker exchange allows participants to learn from each other by solving problems in their small groups.

Worker-to-Trainer: Lecture-style training assumes that the trainer knows all the answers. With SGAM it is understood that the trainers also have a lot to learn and this is the purpose of the worker-to-trainer exchange. It occurs during the report-back and it is designed to give the trainer an opportunity to learn from the participants.

Trainer-to-Worker: This is the trainer's opportunity to clear up confusion and make points they think are key. By waiting until the summary section, trainers know better what people need to know.

Chemical Hazards

Purpose

To analyze areas in the workplace where the risks of chemical exposures are greatest.

To understand the different ways for workers to become familiar with the hazardous chemicals in their workplace.

To evaluate the importance, use and limits of personal protective equipment (PPE) in preventing hazardous chemical exposures.



Task One

Step 1:

Review the factsheets on pages 10 to 13.

Step 2:

Make a drawing on the sheet of flip chart paper that shows the basic layout of your workplace. See page 13 for an example of what a drawing looks like. Use the entire sheet of paper for your map.

Step 3:

Identify the chemical hazards in each area of the facility using the hazard code key on page 11 and a colored sticker.

Step 4:

Label each chemical hazard with a name or brief description.

Step 5:


Based on your map make a list of the chemical hazards that concern you the most and be ready to tell us why these chemical hazards are a concern for your group.

1. Use Hazard Mapping to Identify Chemical Exposures


A hazard map is a visual representation of the workplace that identifies where there are chemical hazards that could cause injuries or illness to workers.

Hazard mapping draws on what workers know from on-the-job experience and respects the vast array of skills, experience, and knowledge that workers have about their jobs.

The hazard mapping approach works best when conducted by a small group of workers from the same department of work area and requires working the small group to work together to identify, prioritize, and solve problems



2. Chemical Hazards Code Key



Color	Type of Chemical Hazard	Examples	
Blue	Solid chemical hazards – chemicals in solid form	Dry paint (dry paint can contain lead)	
Green	Dusts chemical hazards – Dust are small particles of solids. Workers can be exposed to materials that are already in dust form, or through work processes that create these dust.	Cement bags, fiberglass, asbestos	
Red	Liquid chemical hazards – These are chemicals that are found in liquid form at room temperature.	Pesticides, paints, cleaning products	
Orange	Vapors as chemical hazards – Vapors are gases that have evaporated. Certain vapors can cause eye and skin irritation. Some can even cause brain damage over time.	Pesticides, paints, cleaning products	
Yellow	Gases as chemical hazards – Some chemicals exist as gases at room temperature. Other solid or liquid chemicals converted to gases when they are heated.	Aerosols, carbon monoxide, vehicle fumes, hydrogen sulfide.	

3. Identifying Areas of Concern


Before you begin developing your map, think about where chemical hazards may exist in your workplace.

Potential Locations of Chemical Hazards	
When measuring or sampling	
Transferring hazardous materials	
Packaging and unpacking of hazardous materials	
Operations involving hazardous materials such as welding,	
machining, plating, spray coating, using cleaning solvents, etc	
Maintenance activities involving hazardous materials	
Spills	

Source: Health and Safety in the Workplace: Instructional Guide: Interfaith Worker Justice, 2010.



4. Example of a Home Hazard Map



Task Two

In your groups, read the case study below and review the factsheets on pages 17 to 21. Then working together, use the factsheets and your own experience to answer the questions on the next page.

Maria works in the kitchen of a restaurant as a dishwasher. To clean cooking pans, she soaks them in a powerful cleaning solution. She uses liquid resistant gloves to protect her hands and arms.

One day, as Maria was lifting three large pans out of the cleaning solution at once, the pans slipped out of her hands and back into the solution, which splashed all over the side of her face and into her left eye. She was blind in one eye for two weeks. Maria was lucky...she got her eyesight back. The labels on the next page were attached to the chemicals that she was using.

Source: Adapted from http://www.ccohs.ca/teach_tools/chem_hazards/case_studies.html



Ammonia (Anhydrous)

DANGER

Fatal if inhaled. Causes severe skin burns and eye damage. Contains gas under pressure; may explode if heated. Very toxic to aquatic life.

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately. Skin Contact (or Hair): Remove/Take off immediately all contaminated clothing. Rinse Skin with water/shower. Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen Seek medical advice.

Store in a locked cabinet. Protect from sunlight. Store in a well-ventilated place.

See Material Safety Data Sheet for further details regarding safe use of this product.

ABC Chemical Supply

123 Nearby Blvd. Anytown, US 12345

(987) 654-3210







May cause fire or explosion; strong oxidizer Causes severe skin burns and eye damage

Keep away from heat. Keep away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles. Wear protective neoprene gloves, safety goggles and face shield with chin guard. Wear fire/flame resistant clothing. Do not breathe dust or mists. Wash arms, hands and face thoroughly after handling. Store locked up. Dispose of contents and container in accordance with local, state and federal regulations.

First aid:

IF ON SKIN (or hair) or clothing⁶: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Immediately call poison center.

Specific Treatment: Treat with doctor-prescribed burn cream.

Fire:

In case of fire: Use water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Great Chemical Company, 55 Main Street, Anywhere, CT 064XX

Telephone (888) 777-8888

1.	What is the signal word for each of the chemicals? What do the words mean?
2.	What are the precautionary steps in regard to the chemicals?
3.	What are first aid measures that a worker should take if exposed to the chemicals?
4.	What are the names of the pictograms associated with each chemical?

1. Safety Data Sheets (SDS)

Safety Data Sheets (SDSs), which must accompany hazardous chemicals, are the more complete resource for details regarding hazardous chemicals. Every employer whose workplace using hazardous chemicals is required to keep SDS related to each chemical used in the workplace.

The SDS gives information about the hazards associated with the chemicals and ways for workers to protect themselves from harm while using them.

Workers have a right to request and read the SDS of the chemical that they handle.

Employers are not required to have SDS in languages other than English.

Source: Health and Safety in the Workplace: Instructional Guide: Interfaith Worker Justice, 2010.

2. Labels

Containers of hazardous chemicals must have a label printed on it or attached to it. The label provides information to workers on the specific hazardous chemical. The label must contain the following information:

Product Identifier –

The chemical name or code number of the chemical.

Name,
Address
and
Telephone
Number –
Information
about the
chemical
manufacturer
of the
chemical.

Signal Word – Used to indicate the relative level of severity of the hazard and alert the work to a potential hazard. "Danger" and "Warning" are the only two words used as signal words. "Danger" is used for more severe hazards. "Warning" is used for less

severe hazards. Hazard Pictograms Supplier al Code Identification Keep container tightly closed. Store in a cool, well-ventilated place that is locked. Keep away from heal/sparks/open flame. No smol Only use nor-sparking tool only use nor-sparking tool. Use explosion-proof electrical equipment. Danger Take precautionary measures against static discharge Bround and bond container and receiving equipment. Statements nk or smoke when using horoughly after handling accordance with local, n egulations as specified. Statements Supplemental Information Directions for Use First Aid First Aid
If exposed call Poison Center.
If on skin for hair! Take off immediately any co-clothing. Rinse skin with water. Fill weight:

Precautionary Statement(s) – Describe recommended measures that should be taken to minimize or prevent adverse effects resulting from exposure to the hazardous chemical or improper storage or handling. There are four types or precautionary statements: prevention (to minimize exposure); response (in case of accidental spillage or exposure emergency response, and first-aid); storage; and disposal.

Pictogram(s) -

Graphic symbols used to communicate specific information about the hazards of a chemical.

> Hazard Statement(s) – Describe the nature of the hazards of a chemical and the degree of the hazards. For example, "Causes damage to kidneys through prolonged exposure when absorbed through the skin."

Source: OSHA Brief - Hazard Communication Standard: Labels

3. Pictograms

Pictograms are graphic symbols used to communicate specific information about the hazards of a chemical.

Flame Over Circle



Oxidizers

Exploding Bomb



Explosives Self-Reactives Organic Peroxides

Exclamation Mark



Irritant (skin and eyes)
Skin Sensitizer
Acute Toxicity (harmful)
Narcotic Effects
Respiratory Tract
Irritant
Hazardous to Ozone Layer

Health Hazard



Carcinogen
Mutagenicity
Reproductive Toxicity
Respiratory Sensitizer
Target Organ Toxicity
Aspiration Toxicity

Flame



Flammables
Pyrophorics
Self-Heating
Emits Flammable Gas
Self-Reactives
Organic Peroxides



Gas Cylinder

Gases Under Pressure

Corrosion



Skin Corrosion
Burns
Eye Damage
Corrosive to Metals



Skull and Crossbones

Acute Toxicity (fatal or toxic)

Source: OSHA Brief - Hazard Communication Standard: Labels

Task Three

Step 1:

Review the factsheets on pages 23 to 26.

Step 2:

Using the large sheet of paper with and draw an outline of a body (front and back) like the one on page 43. Use the entire sheet of paper for your body map.

Step 3:

Identify on the body where potential types of chemical exposures that you could suffer as a result of your work with hazardous chemicals using the color-coded key on page 24 and a colored sticker.

Step 4:

Label each hazard exposure with a name or brief description.

Step 5:

Based on your map make a list of the chemical exposures that concern you the most and be ready to tell us why these are a concern for your group.

1. Using Body Mapping to Chemical Exposures

A body map is a drawing that shows what parts of your body are vulnerable to chemical exposures.

A body map draws on what workers know from on-the-job experience and respects the vast array of skill, experience and knowledge that workers have about their jobs.

The body mapping approach works best when conducted by a small group of workers from the same department of work area and requires working the small group to work together to identify, prioritize and solve problems.



2. Chemical Hazards Code Key


Color	Type of Chemical Hazard	Examples
Blue	Solid chemical hazards – chemicals in solid form	Dry paint (dry paint can contain lead)
Green	Dusts chemical hazards – Dust are small particles of solids. Workers can be exposed to materials that are already in dust form, or through work processes that create these dust.	Cement bags, fiberglass, asbestos
Red	Liquid chemical hazards – These are chemicals that are found in liquid form at room temperature.	Pesticides, paints, cleaning products
Orange	Vapors as chemical hazards – Vapors are gases that have evaporated. Certain vapors can cause eye and skin irritation. Some can even cause brain damage over time.	Pesticides, paints, cleaning products

Color	Type of Chemical Hazard	Examples
Yellow	Gases as chemical hazards – Some chemicals exist as gases at room temperature. Other solid or liquid chemicals converted to gases when they are heated.	Aerosols, carbon monoxide, vehicle fumes, hydrogen sulfide.


3. Routes of Exposure to Chemical Hazards

Potential Routes of Exposure to Chemical Hazards		
Inhalation	Breathing in contaminated air (dust, fumes, mist, smoke)	
Absorption	Skin contact where chemicals can pass through the skin into	
_	the blood stream	
Ingestion	Chemicals swallowed accidentally if food, cigarettes or hands	
	are contaminated	
Injection	A sharp object such as a needle punctures the skin and injects	
-	chemicals into the blood stream	

Source: Health and Safety in the Workplace: Instructional Guide. Interfaith Worker Justice, 2010.



4. Example of a Body Map



Task Four

In your groups, observe the pieces of Personal Protective Equipment that is in the box for your group. Working together in groups, use the factsheet on page 29, your body map from the previous activity, the labels on the next page, and your own experience to answer the following questions. Then, choose a worker from the group and dress the worker with the Personal Protective Equipment from the box.

Type of Hazard	The part of the body potentially affected by the hazard	The type of Personal Protective Equipment (PPE) that could be used for the hazard





Fatal if inhaled. Causes severe skin burns and eye. damage. Contains gas under pressure; may explode if heated. Very toxic to aquatic life.

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately. Skin Contact (or Hair): Remove/Take off immediately all contaminated clothing. Rinse Skin with water/shower Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen Seek medical advice

Store in a locked cabinet. Protect from sunlight. Store in a well-ventilated place.

See Material Safety Data Sheet for further details regarding safe use of this product.

ABC Chemical Supply

123 Nearby Blvd. Anytown, US 12345

(987) 654-3210

OXI252 (disodiumflammy)





May cause fire or explosion; strong oxidizer Causes severe skin burns and eye damage

Keep away from heat. Keep away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles. Wear protective neoprene gloves, safety goggles and face shield with chin guard. Wear fire/flame resistant clothing. Do not breathe dust or mists. Wash arms, hands and face thoroughly after handling. Store locked up. Dispose of contents and container in accordance with local, state and federal regulations.

IF ON SKIN (or hair) or clothing⁶: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Immediately call poison center.

Specific Treatment: Treat with doctor-prescribed burn cream.

Fire:

In case of fire: Use water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Great Chemical Company, 55 Main Street, Anywhere, CT 064XX

Telephone (888) 777-8888

1. Personal Protective Equipment and Chemical Hazards

The type of Personal Protective Equipment (PPE) a worker requires in order to work with a particular chemical is outlined in the Safety Data Sheets (SDS).

PPE is the least efficient way to protect workers because it does not get rid of the hazardous situation. If equipment fails, workers are still exposed to the risk.

Summary

The point of hazard mapping is to gather the knowledge about chemical hazards from groups of workers so that workers can together eliminate and/or reduce the risks of accidents and injuries.

Chemical hazards can be found in the following forms: solid chemical hazards, dust particles as chemical hazards, liquid chemical hazards, vapors and gases as chemical hazards.

The Safety Data Sheet (SDS) gives information about the hazards associated with the chemicals and ways for workers to protect themselves from harm while using them.

A label must be printed on containers of hazardous chemicals that provides information to workers on the specific hazardous chemical.

Pictograms are graphic symbols used to communicate specific information about the hazards of a chemical.

A body map is a picture that shows what parts of your body can be exposed to chemical hazards and what those chemical hazards are.

Personal Protective Equipment (PPE) is the least efficient way to protect workers because it does not get rid of the hazardous situation. If equipment fails, workers are still exposed to the risk.

Machine Hazards

Purpose

To analyze areas in the workplace where the risks injuries due to machine hazards are greatest.

To understand the different ways to control machine hazards in the workplace.

To understand the importance of lockout/tagout procedures in preventing amputations and injuries.



Task One

Step 1:

Review the factsheets on pages 33 to 37.

Step 2:

Make a drawing on the sheet of flip chart paper that shows the basic layout of your workplace. See page 37 for an example of what a drawing looks like). Use the entire sheet of paper for your map.

Step 3:

Identify the machine hazards in each area of the facility using the hazard code key on pages 35-36 and a colored sticker.

Step 4:

Label each hazard with a name or brief description.

Step 5:

Based on your map make a list of the hazards that concern you the most and be ready to tell us why these hazards are a concern for your group.

1. Use Hazard Mapping to Identify Machine Hazards

A hazard map is a visual representation of the workplace that identifies where there are machine hazards that could cause injuries or amputations to workers.

Hazard mapping draws on what workers know from on-the-job experience and respects the vast array of skill, experience and knowledge that workers have about their jobs.

The hazard mapping approach works best when conducted by a small group of workers from the same department of work area and requires working the small group to work together to identify, prioritize and solve problems.

2. Machine Hazards

Employee exposure to unguarded or inadequately guarded machines is prevalent in many workplaces. Consequently, workers who operate and maintain machinery suffer approximately 18,000 amputations, lacerations, crushing injuries, abrasions, and over 800 deaths per year. Amputation is one of the most severe and crippling types of injuries in the occupational workplace, and often results in permanent disability.

All machines consist of three fundamental areas:

- 1. the point of operation where work is performed on the material, such as cutting, shaping, boring, or forming of a product.
- 2. the power transmission device all components of the mechanical system which transmit energy to the part of the machine performing the work including flywheels, pulleys, belts, connecting rods, couplings, cams, spindles, chains, cranks, and gears.
- 3. the operating controls A mechanical or electrical power control on each machine to make it possible for the worker to cut off the power from each machine without leaving his or her position at the point of operation.

Despite all machines having the same basic components, their safeguarding needs widely differ due to varying physical characteristics and operator involvement.


Source: OSHA Machine Guarding e-tool

https://www.osha.gov/SLTC/etools/machineguarding/intro.html


3. Machine Hazards Code Key

Color	Type of Machine Hazard
Blue	Rotating – can be dangerous; even smooth, slowly rotating shafts can grip hair and clothing, and through minor contact force the hand and arm into a dangerous position. Injuries due to contact with rotating parts can be severe. Collars, couplings, cams, clutches, flywheels, shaft ends, spindles, meshing gears, and horizontal or vertical shafting are some examples of common rotating mechanisms which may be hazardous. The danger increases when projections such as set screws, bolts, nicks, abrasions, and projecting keys or set screws are exposed on rotating parts.
Red	Reciprocating – may be hazardous because, during the back-and-forth or up-and-down motion, a worker may be struck by or caught between a moving and a stationary part.
Orange	Transversing – (movement in a straight, continuous line) creates a hazard because a worker may be struck or caught in a pinch or shear point by the moving part.
Purple	Pinching – results when power is applied to a slide for the purpose of blanking, drawing, or stamping metal or other materials. The danger of this type of action occurs at the point of operation where material is inserted, held, and withdrawn by hand. Typical machines used for punching operations are power presses and iron workers.

Color	Type of Machine Hazard
Black	Shearing – involves applying power to a slide or knife in order to trim or shear metal or other materials. A hazard occurs at the point of operation where material is actually inserted, held, and withdrawn. Examples of machines used for shearing operations are mechanically, hydraulically, or pneumatically powered shears.
Brown	Bending – results when power is applied to a slide in order to draw or stamp metal or other materials. A hazard occurs at the point of operation where stock is inserted, held, and withdrawn. Equipment that uses bending action includes power presses, press brakes, and tubing benders.



4. Example of a Home Hazard Map



Task Two

Working together in your groups, choose one type of hazard control from page 43. Then use the factsheets and your own experience to make a poster about the control to present to the rest of the group.

Then using the hazard maps that your developed in the previous activity, choose one or two hazards from the map that you believe are important. Then as a group prepare a short skit that demonstrates workers approaching their employer to discuss ways that the employer can control the workplace hazard. At least one of the hazard control methods and machine guard examples should be incorporated in the skit.

Step 1:

Working together in your groups, choose one type of hazard control from page 40. Then use the factsheets on pages 39 - 42 and your own experience to make a poster about the control to present to the rest of the group.

Step 2:

Using the hazard maps that your developed in the previous activity, choose one or two hazards from the map that you believe are important.

Step 3:


As a group prepare a short skit that demonstrates workers approaching their employer to discuss ways that the employer can control the workplace hazard. At least one of the hazard control methods from page 42 and machine guard examples from page 41 - 42 should be incorporated in the skit.

1. Hierarchy of Controls

OSHA requires employers to eliminate, substitute or use engineering controls to reduce hazardous conditions on the job.

Employers must apply these *higher-level controls* before resorting to the use of *lower level controls* such as warnings, training and procedures and the use of personal protective equipment (PPE).

It is important to recognize that **personal protective equipment** (PPE) is the least effective way to control a hazard.



2. Types of Hazard Controls

Hierarchy of Controls			
Least Effective (Worst) More Effective (Best)	Elimination	Elimination - The best way to control a hazard.	
		Best to do this as early as possible.	
		An example of elimination would be to use an electric forklift truck rather than a gas operated forklift truck to eliminate carbon monoxide in a warehouse.	
	Substitution	Substitution – Used when a hazard cannot be eliminated completely.	
		The idea is to substitute chemicals, equipment, or hazardous materials with ones that are less hazardous.	
		An example of this would be using paint that does not contain lead-based pigments. A potential problem is when the product being used as a substitute is as dangerous as the original. For this reason, it is important to find out if the product is truly less hazardous than the original.	
	Engineering	Engineering - using technology to change the work environment, a machine, or some equipment in order to reduce the hazard.	
		For example, machine guards, backup alarms, guardrails, covers, slip resistant surfaces, and using machines to move heavy objects instead of carrying them.	
	Administrative	Administrative Controls - Changing the way and the structure of how work is done.	
		Example: Instead of one employee exposed to a particular hazard for eight hours a day, the employer could assign four workers to work for two hours each. This could be used for repetitive tasks or for any exposure to a chemical hazard.	
	Personal Protective Equipment	Personal protective equipment (PPE) – the least efficient way to protect workers because it does not get rid of the hazard. If equipment fails, workers are still exposed to the risk.	
	(PPE)	Examples include protective wear for the eyes, ears, and face, gloves, and protective clothes.	


3. Machine Guarding

Machine guards are barriers which prevent access to machine danger areas.

There are four general types of machine guards:

Fixed Guarding	Provides a fixed barrier to machine danger areas.
Junung	Is a permanent part of the machine.
	Is not dependent of moving parts of the machine to function.
	Preferable to all other types because of its relative simplicity.
Interlocking	Shuts off or disengages power, stops the moving parts and prevents
Guarding	starting of the machine when the guard is open; should require the
	machine to be stopped before the worker can reach into the danger area.
	When this type of guard is opened or removed, the tripping mechanism
	and/or power automatically shuts off or disengages, the moving parts of
	the machine are stopped, and the machine cannot cycle or be started until
	the guard is back in place.
	Can provide maximum protection
	Allows access to the machine for removing jams without time consuming
	removal of the fixed guards
Adjustable	Provides a barrier that may be adjusted to facilitate a variety of production
Guarding	operations.
	Adjustable guards are useful because they allow flexibility in
	accommodating various sizes of stock.
	Hands may enter danger area - protection may not be complete at all
	times.

Fixed	Provides a fixed barrier to machine danger areas.
Guarding	
	Is a permanent part of the machine.
	Is not dependent of moving parts of the machine to function.
	Preferable to all other types because of its relative simplicity.
C 16	
Self-	This guard protects the operator by placing a barrier between the danger
Adjustable	area and the operator.
Guarding	Provides a barrier that moves according to the size of the stock entering
	the danger area.
	the duniger dream
	As the operator moves the stock into the danger area, the guard is pushed
	away, providing an opening which is only large enough to admit the stock.
	After the stock is removed, the guard returns to the rest position.
	Does not always provide maximum protection
	Does not always provide maximum protection



Task 3

In your groups, read the two case studies below and review the factsheets pages 45 - 49. Then working together, use the factsheets and your own experience to answer the questions on the next page.

Case Study 1

In preparation for the next day's work, a clean-up crew was using a high-pressure water hose to clean machines in a poultry plant. One of the two workers was preparing to wash down a feather-picking machine, and the other was washing down a scalder machine. The first employee cranked on his machine to get inside and wash out feathers that had lodged throughout the machine during the feather picking process. Electric cords were pinched between the metal crank and the metal frame of this machine, and the insulation on the cords was pierced. As a result, an energized conductor was contacting the metal frame of the machine. Because the machine was turned off at the time, the workers were unaware of the condition of the cord. The first employee then moved between the two machines to begin the wash down. When he contacted the energized machine frame, he was electrocuted. His coworker received an electric shock when he tried to pull the first employee from the area. The second employee was hospitalized for his injury.

Case Study 2

A sanitation worker at a poultry plant was cleaning out a chiller machine. The motor that powers the paddles inside the chiller was accidentally turned on by a coworker who was cleaning a different chiller. Neither the main power control nor the chiller control box had been locked or tagged out. The employee was struck by and caught between the rotating paddle blades and the interior wall of the chiller. He died of severe chest injuries approximately 28 hours after the accident.

1.	What was the main hazardous situation that caused the fatality or injury in the case studies above?
2.	What could have been done to prevent the fatality or injury in the case studies above?
3.	What possible solutions to the hazardous situations are available to the workers in the case studies above?
4.	Are you familiar with your employer's lockout/tagout procedures? Have you received training from your employer on these procedures?

1. Lockout/Tagout Procedures

Many times when workers remove guards or machine components to effectively clean or maintenance equipment they are exposed to hazardous energy from the machines.

In order to isolate the machine or equipment from its energy sources, lockout/tagout procedures are used.

Lockout/tagout procedures help ensure that a machine or equipment is disconnected from its energy source and will not operate while a worker is cleaning the machine.

Before a worker begins to clean a machine or equipment, steps must be taken to ensure that the machine or equipment is completely disconnected from its energy source and locked our tagged out.

Sometime, the machine or equipment must be re-energized for a limited period of time for testing or repositioning purposes. During the testing or positioning period, it is important to make sure other workers are protected from the machine or equipment's hazardous energy. Once the machine or equipment has been positioned, the equipment or machine must be disconnected and locked or tagged out before cleaning continues.


2. Cuts, Lacerations, and Amputations

Hazardous Situation:

As workers remove blades or other components from cutting equipment, they may receive cuts or lacerations. Any cut not treated at once will normally become infected as a result of working with poultry.

Possible Solutions:

- Use equipment lockout/tagout procedures.
- Provide cut-resistant gloves to workers who remove blades from equipment.



3. Struck By, Struck Against and Caught In

Hazardous Situation:

Workers cleaning or providing maintenance to powered equipment can get caught in the equipment if the motor is turned on. Serious injury or death can result.

Possible Solutions:

Use the following effective protection for minor cleaning or maintenance jobs that are routine, repetitive and performed as an essential part of the production process:

- Use energy control lockout/tagout procedures.
- Use interlocked barrier guards/gates.
- Use properly designed control switches or buttons that are placed in the open/off safe positions when the devices are under the exclusive control of the employee performing the task.
- Know the location and use of the control circuit devices.

4. Falls From Ladders or Equipment

Hazardous Situation:

Workers climb on ladders or equipment to adequately reach all surfaces for cleaning and/or maintenance. Falls can result in fractures or contusions.

Possible Solutions:

- Make sure platforms or portable ladders are the appropriate size and height for the job and in good condition.
- Do not climbing on equipment.

5. Electric Shock

Hazardous Situation:

Workers may experience electrical shock from water contacting electrical connections or switch boxes or from improper reassembly of electric connections after disassembly for cleaning or maintenance.

Possible Solutions:

- Lockout and tag the electric circuit when it is possible to do so.
- Use and maintain proper wiring and grounding.
- Make sure all electrical boxes are covered.
- Use equipment approved for wet locations.
- Inspect for worn or improperly maintained electrical fixtures and equipment.
- Source: U.S. Department of Labor, Occupational Safety and Health Administration, Poultry Processing Industry e-tool for Sanitation Workers

Summary

Workers who operate and maintain machinery suffer approximately 18,000 amputations, lacerations, crushing injuries, abrasions, and over 800 deaths per year. Amputation is one of the most severe and crippling types of injuries in the occupational workplace, and often results in permanent disability.

Machines can present several types of hazards including: rotating, reciprocating, transversing, cutting, pitching, shearing, and bending hazards.

OSHA requires employers to eliminate, substitute or use engineering controls to reduce hazardous conditions on the job.

Personal protective equipment (PPE) is the least effective way to control a hazard.

Machine guards are barriers which prevent access to machine danger areas.

Lockout/tagout procedures help ensure that a machine or equipment is disconnected from its energy source and will not operate while a worker is cleaning the machine.

Lockout/tagout procedures can help prevent a variety of injuries such as cuts, lacerations, amputations, electrical shock, getting stuck or caught in machinery or even death caused by hazardous situations.