# **Training and Education Material FY 2019**

Student Silica Exposure Hand-out

**DISCLAIMER**: This material was produced under grant number SH-05058-SH8 from the U.S. Department of Labor, Occupational Safety and Health Administration. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does mention of trade names, commercial products, or organizations imply endorsement by the U.S. Government. The U.S. Government does not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed.

**Trainees:** Circle each task, materials and occupation that best fits your past or current experience with silica exposure. Upon completion of this assignment, the class will discuss their experiences with each other.

### Industry

- 1. Abrasive blasting
- 2. pavement manufacturing
- 3. Blast furnaces
- 4. Cement manufacturing
- 5. Ceramics, clay, and pottery
- 6. Concrete mixing
- 7. Concrete Asphalt tunneling
- 8. Construction (mainly cement, concrete work)
- 9. Demolition
- 10. Electronics industry
- 11. Foundry industry: grinding, molding, shakeout, core room (High Risk)
- 12. Hand molding, casting, and forming
- 13. Jack hammer operations
- 14. Manufacturing abrasives, paints, soaps, and glass
- 15. Mining
- 16. Repair or replacement of linings of rotary kilns and cupola furnaces
- 17. Rolling and finishing mills
- 18. Sandblasting (High Risk)
- 19. Setting, laying, and repairing railroad track
- 20. Steelwork
- 21. Stone, brick, and concrete block cutting, blasting, chipping, grinding, and sawing
- 22. Tunneling operations

## Materials

- 1. Abrasives
- 2. Coal Dust
- 3. Concrete
- 4. Filter Aids
- 5. Graphite, natural
- 6. Mica
- 7. Mineral Products
- 8. Paints
- 9. Pavement
- 10. Perlite
- 11. Plant Materials
- 12. Plastic Fillers

- 13. Polishing Compounds
- 14. Portland Cement
- 15. Sands
- 16. Silicates
- 17. Slag
- 18. Soapstone
- 19. Soil

#### Occupation

- 1. Brickmason / stonemason
- 2. Blasting/drilling
- 3. Construction laborer
- 4. Crane and tower operator
- 5. Crushing and grinding machine operator
- 6. Drywall installation
- 7. Furnace, kiln, non-food oven operator
- 8. Heavy Equipment operator
- 9. Grinding, abrading, buffing, and polishing machine operator
- 10. Hand molder/shaper (not jeweler)
- 11. Heavy-equipment mechanic
- 12. Janitor or cleaner
- 13. Machinist
- 14. Metals/plastics machine operator
- 15. Molding and casting machine operator
- 16. Mining machine operator
- 17. Miscellaneous material moving equipment operator
- 18. Millwright
- 19. Operating engineer
- 20. Painter who sandblasts (High Risk)
- 21. Production supervisor
- 22. Rock driller (High Risk)
- 23. Roof bolter (High Risk)
- 24. Sandblaster (High Risk)
- 25. Steelworker

Trainees will review (Table I) standards as it relates to the specific task and materials listed above.

# 29 CFR 1926 Respirable crystalline silica (Table 1) for exposure controls

Table 1: Specified Exposure Control Methods When Working With Materials Containing Crystalline Silica

| Construction Task or<br>Equipment Operation |  | Engineering and Work Practice Control  | Required Respiratory<br>Protection  |   |
|---|--|--|---|---|
|   |  | Methods  | ≤ 4 hours/shift   | >4 hours/shift  |
| 1   | Stationary masonry<br>saws   | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | None  | None  |
| 2a  | Handheld power saws<br>(any blade diameter)<br>when used outdoors  | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | None  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 2b  | Handheld power saws<br>(any blade diameter)<br>when used indoors or<br>in an enclosed area   | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 3   | Handheld power<br>saws for cutting<br>fiber-cement board<br>(with blade diameter<br>of 8 inches or less)<br>for tasks performed<br>outdoors only | <ul> <li>Use saw equipped with commercially available dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency.</li> </ul> | None  | None  |
| 4a  | Walk-behind saws<br>when used outdoors   | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | None  | None  |
| 4b  | Walk-behind saws<br>when used indoors or<br>in an enclosed area  | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 5   | Drivable saws for tasks<br>performed outdoors<br>only  | <ul> <li>Use saw equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the blade.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | None  | None  |
| 6   | Rig-mounted core saws<br>or drills   | <ul> <li>Use tool equipped with integrated water<br/>delivery system that supplies water to cutting<br/>surface.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>  | None  | None  |

| Construction Task or<br>Equipment Operation |  | Engineering and Work Practice Control<br>Methods   | Required Respiratory<br>Protection<br>≤ 4 hours/shift >4 hours/shift        |   |
|---|--|--|---|---|
| 7   | Handheld and stand-<br>mounted drills<br>(including impact and<br>rotary hammer drills)              | <ul> <li>Use drill equipped with commercially available shroud or cowling with dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.</li> <li>Use a HEPA-filtered vacuum when cleaning holes.</li> </ul> | None  | None  |
| 8   | Dowel drilling rigs for<br>concrete for tasks<br>performed outdoors<br>only                          | <ul> <li>Use shroud around drill bit with a dust collection system.</li> <li>Dust collector must have a filter with 99% or greater efficiency and a filter cleaning mechanism.</li> <li>Use a HEPA-filtered vacuum when cleaning holes.</li> </ul>   | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 9a  | Vehicle-mounted<br>drilling rigs for rock and<br>concrete  | <ul> <li>Use dust collection system with close capture<br/>hood or shroud around drill bit with a low-flow<br/>water spray to wet the dust at the discharge<br/>point from the dust collector.</li> </ul>  | None  | None  |
| 9b  | Vehicle-mounted<br>drilling rigs for rock and<br>concrete  | <ul> <li>Operate from within an enclosed cab and use<br/>water for dust suppression on drill bit.</li> </ul>   | None  | None  |
| 10a   | Jackhammers and<br>handheld powered<br>chipping tools when<br>used outdoors                          | <ul> <li>Use tool with water delivery system that<br/>supplies a continuous stream or spray of water<br/>at the point of impact.</li> </ul>  | None  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 10b   | Jackhammers and<br>handheld powered<br>chipping tools when<br>used indoors or in an<br>enclosed area | <ul> <li>Use tool with water delivery system that<br/>supplies a continuous stream or spray of water<br/>at the point of impact.</li> </ul>  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 10c   | Jackhammers and<br>handheld powered<br>chipping tools when<br>used outdoors                          | <ul> <li>Use tool equipped with commercially available shroud and dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.</li> </ul>   | None  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 10d   | Jackhammers and<br>handheld powered<br>chipping tools when<br>used indoors or in an<br>enclosed area | <ul> <li>Use tool equipped with commercially available shroud and dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide the air flow recommended by the tool manufacturer, or</li> </ul>  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |

| Construction Task or<br>Equipment Operation |   | Engineering and Work Practice Control<br>Methods   | Required Respiratory<br>Protection<br>≤ 4 hours/shift >4 hours/shift        |   |
|---|---|--|---|---|
|   | *   | greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.   | *   | *   |
| 11  | Handheld grinders for<br>mortar removal (i.e.,<br>tuckpointing)   | <ul> <li>Use grinder equipped with commercially available shroud and dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.</li> </ul> | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask | Powered Air-<br>Purifying<br>Respirator<br>(PAPR) with<br>P100 Filters      |
| 12a   | Handheld grinders for<br>uses other than mortar<br>removal for tasks<br>performed outdoors<br>only        | <ul> <li>Use grinder equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the grinding surface.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>  | None  | None  |
| 12b   | Handheld grinders for<br>uses other than mortar<br>removal when used<br>outdoors                          | <ul> <li>Use grinder equipped with commercially available shroud and dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.</li> </ul> | None  | None  |
| 12c   | Handheld grinders for<br>uses other than mortar<br>removal when used<br>indoors or in an<br>enclosed area | <ul> <li>Use grinder equipped with commercially available shroud and dust collection system.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.</li> </ul> | None  | N95 (or<br>Greater<br>Efficiency)<br>Filtering<br>Facepiece or<br>Half Mask |
| 13a   | Walk-behind milling<br>machines and floor<br>grinders   | <ul> <li>Use machine equipped with integrated water<br/>delivery system that continuously feeds water<br/>to the cutting surface.</li> <li>Operate and maintain tool in accordance with<br/>manufacturer's instructions to minimize dust<br/>emissions.</li> </ul>   | None  | None  |
| 13b   | Walk-behind milling<br>machines and floor<br>grinders   | <ul> <li>Use machine equipped with dust collection system recommended by the manufacturer.</li> <li>Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.</li> <li>Dust collector must provide the air flow recommended by the manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.</li> </ul>   | None  | None  |

| Construction Task or<br>Equipment Operation |   | Engineering and Work Practice Control<br>Methods   | Required Respiratory<br>Protection<br>≤ 4 hours/shift >4 hours/shift |      |
|---|---|--|--|------|
|   | *   | <ul> <li>When used indoors or in an enclosed area, use<br/>a HEPA-filtered vacuum to remove loose dust<br/>in between passes.</li> </ul>   | *  | *    |
| 14  | Small drivable milling<br>machines (less than<br>half-lane)   | <ul> <li>Use a machine equipped with supplemental water sprays designed to suppress dust.</li> <li>Water must be combined with a surfactant.</li> <li>Operate and maintain machine to minimize dust emissions.</li> </ul>  | None   | None |
| 15a   | Large drivable milling<br>machines (half-lane<br>and larger) for cuts of<br>any depth on asphalt<br>only  | <ul> <li>Use machine equipped with exhaust<br/>ventilation on drum enclosure and<br/>supplemental water sprays designed to<br/>suppress dust.</li> <li>Operate and maintain machine to minimize<br/>dust emissions.</li> </ul>   | None   | None |
| 15b   | Large drivable milling<br>machines (half-lane<br>and larger) for cuts of<br>four inches in depth or<br>less on any substrate  | <ul> <li>Use machine equipped with exhaust ventilation on drum enclosure and supplemental water sprays designed to suppress dust.</li> <li>Operate and maintain machine to minimize dust emissions.</li> </ul>   | None   | None |
| 15c   | Large drivable milling<br>machines (half-lane<br>and larger) for cuts of<br>four inches in depth or<br>less on any substrate  | <ul> <li>Use a machine equipped with supplemental water spray designed to suppress dust.</li> <li>Water must be combined with a surfactant.</li> <li>Operate and maintain machine to minimize dust emissions.</li> </ul>   | None   | None |
| 16  | Crushing machines   | <ul> <li>Use equipment designed to deliver water spray<br/>or mist for dust suppression at crusher and<br/>other points where dust is generated (e.g.,<br/>hoppers, conveyers, sieves/sizing or vibrating<br/>components, and discharge points).</li> <li>Operate and maintain machine in accordance<br/>with manufacturer's instructions to minimize<br/>dust emissions.</li> <li>Use a ventilated booth that provides fresh,<br/>climate-controlled air to the operator, or a<br/>remote control station.</li> </ul> | None   | None |
| 17a   | Heavy equipment and<br>utility vehicles used to<br>abrade or fracture<br>silica-containing<br>materials (e.g., hoe-<br>ramming, rock ripping)<br>or used during<br>demolition activities<br>involving silica-<br>containing materials | Operate equipment from within an enclosed cab.   | None   | None |
| 17b   | Heavy equipment and<br>utility vehicles used to<br>abrade or fracture<br>silica-containing<br>materials (e.g., hoe-<br>ramming, rock ripping)<br>or used during<br>demolition activities<br>involving silica-<br>containing materials | <ul> <li>When employees outside of the cab are<br/>engaged in the task, apply water and/or dust<br/>suppressants as necessary to minimize dust<br/>emissions.</li> </ul>   | None   | None |

| Construction Task or<br>Equipment Operation |   | Engineering and Work Practice Control<br>Methods   | Required Respiratory<br>Protection<br>≤ 4 hours/shift >4 hours/shift |      |
|---|---|--|--|------|
| 18a   | Heavy equipment and<br>utility vehicles for tasks<br>such as grading and<br>excavating but not<br>including demolishing,<br>abrading, or fracturing<br>silica-containing<br>materials | <ul> <li>Apply water and/or dust suppressants as<br/>necessary to minimize dust emissions.</li> </ul>  | None   | None |
| 18b   | Heavy equipment and<br>utility vehicles for tasks<br>such as grading and<br>excavating but not<br>including demolishing,<br>abrading, or fracturing<br>silica-containing<br>materials | <ul> <li>When the equipment operator is the only<br/>employee engaged in the task, operate<br/>equipment from within an enclosed cab.</li> </ul> | None   | None |