

SUSAN HARWOOD TRAINING GRANT PROGRAM FY-2019 Grant Number SH-05149-SH9 This material was produced under a grant (SH-05149-SH9) from the Occupational Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does the mention of trade names, commercial products, or organization imply endorsement by the U.S. Government.

Name \_\_\_\_\_ Date \_\_\_\_\_

## Pre-Test Questions for Excavation and Trench Safety

**Q1: Who is responsible for providing necessary excavation safety training for employees?**

- (a) OSHA
- (b) Employers
- (c) Employees
- (d) Competent person
- (e) Labor union

**Q2: Which two statements are false?**

- (a) Excavation sites should be inspected by a competent person after every rainstorm
- (b) Employers can remove workers from hazardous excavation area, but a competent person cannot authorize excavation work to stop
- (c) If a construction worker notices possible trench collapse hazards in a trench, he/she should leave the trench as soon as possible, since trench collapse happens suddenly
- (d) If a construction worker sees a trench collapse, he/she needs to immediately enter the trench to rescue the trapped or buried workers
- (e) Essentially all trench accidents are preventable through strict compliance with OSHA standards

**Q3: What is the greatest hazard construction workers face when excavation or trenching?**

- (a) Hazardous atmospheres
- (b) Cave-ins
- (c) Falls
- (d) Exposure to falling objects
- (e) Electrocution or explosion

**Q4: What soil has the smallest horizontal angle for sloping or benching protection?**



- (a) Class A
- (b) Class B
- (c) Class C
- (d) Stable Rock

**Q5: In order to quickly exit, at what depth of trenches a ladder or ramp should be present?**

- (a) 4 feet
- (b) 5 feet
- (c) 10 feet
- (d) 12 feet

SUSAN HARWOOD TRAINING GRANT PROGRAM FY-2019 Grant Number SH-05149-SH9 *This material was produced under a grant (SH-05149-SH9) from the Occupational Health Administration, U.S. Department of Labor. It does not necessarily reflect the views or policies of the U.S. Department of Labor, nor does the mention of trade names, commercial products, or organization imply endorsement by the U.S. Government.*

**Q6: Unless made in stable rock, at what depth is a protective system required for a trench?**

- (a) A protective system is never required in trenches
- (b) 5 feet deep or greater
- (c) Any depth if the competent person says so
- (d) Both (b) and (c)

**Q7: Which two statements are false?**

- (a) The top edge of a shielding protection system must be above trench edge
- (b) For safety consideration, excavations should be kept open the minimum amount of time
- (c) It is safe to work in a trench with some standing water
- (d) Construction workers are dangerous under loads handled by lifting equipment
- (e) Under a cubic yard of soil, a construction worker may easily move and escape
- (f) Vibrations from nearby excavator may cause trench collapse

**Q8: What is the minimum distance that excavated soils must be kept from the edge of excavation?**

- (a) As close to the edge as possible for ease of use
- (b) 1 feet
- (c) 2 feet
- (d) 7.5 feet
- (e) 25 feet

**Q9: Name three major types of protective systems in excavation and trench work.**

- (a) Sloping
- (b) Shoring
- (c) Shielding
- (d) Ladders
- (e) Hard Hats

**Q10: What works need to be done before starting to excavate?**

- (a) Evaluate soil type
- (b) Construct protective systems
- (c) Provide safe in and out access
- (d) Prepare an emergency rescue plan
- (e) All of the above