#### \* OSHA ARCHIVE DOCUMENT \* NOTICE: This is an OSHA ARCHIVE Document, and may no longer represent OSHA policy.



**U.S. DEPARTMENT OF LABOR** 

**Occupational Safety and Health Administration** 

# **DIRECTIVE NUMBER:** STD 01-01-010**EFFECTIVE DATE:** 10/22/2019**SUBJECT:**Cancellation of STD 01-01-010, June 30, 1981.

#### ABSTRACT

Purpose:	This Notice cancels OSHA Instruction STD 01-01-010, Heights of Guardrails in General Industry Applications, June 30, 1981.
Scope:	OSHA-wide.
References:	STD 01-01-010, Heights of Guardrails in General Industry Applications, June 30, 1981. Final Rule on Walking-Working Surfaces and Personal Protective Equipment ( <i>Federal Register</i> , November 18, 2016 (81 FR 82494).
Cancellations:	STD 01-01-010, Heights of Guardrails in General Industry Applications, June 30, 1981.
State Impact:	No impact.
Action Offices:	National, Regional, and Area Offices.
Originating Office:	Directorate of Enforcement Programs.
Contact:	Office of General Industry and Agricultural Enforcement 200 Constitution Avenue, NW, N3119 Washington, DC 20210 (202) 693-1850

## \* OSHA ARCHIVE DOCUMENT \* NOTICE: This is an OSHA ARCHIVE Document, and may no longer represent OSHA policy.

By and Under the Authority of

LOREN SWEATT Principal Deputy Assistant Secretary

## \* OSHA ARCHIVE DOCUMENT \* NOTICE: This is an OSHA ARCHIVE Document, and may no longer represent OSHA policy.

### **Executive Summary**

On November 18, 2016, OSHA issued a final rule updating its general industry Walking-Working Surfaces standards. In the preamble, the final rule explicitly rescinds STD 01-01-010 and all subsequent letters of interpretation allowing guardrails to have a minimum height of 36 inches.

\* OSHA ARCHIVE DOCUMENT \* NOTICE: This document is presented here as historical content, for research and review purposes only.